

## **TECHNICAL INFORMATION**

**PRODUCT : KRAFT PAPER LABEL – KL**

For general product labeling applications which very high tear resistance, very high tensile strength and very high bursting resistance required.

### **FACE PAPER**

Type: Brown Kraft Paper

<u>PROPERTY</u>		<u>GENERAL CHARACTERISTIC</u>
Basic weight: 70+/-5 g/m <sup>2</sup>	ISO536	- Very high tensile strength ,very high tear resistance and bursting strength
Caliper: 0.112+/-0.005 mm	ISO534	

### **ADHESIVE**

Type: Acrylic Water Base

<u>PROPERTY</u>		<u>GENERAL CHARACTERISTIC</u>
Adhesion (Stainless Steel): 1.8 kg.f/25mm	FTM2	- Permanent type which high initial tack and high peel adhesive - Good adhesive to metal, plastic, paper, and glass, etc.
Loop tack (Glass): 1.4 kg.f/25mm	FTM9	
Service temperature: min -5°C/ max + 80°C		
Shelf life: 1 year if stored at 22 °C and 50%R.H		

### **LINER**

Type: PE Kraft Release liner

<u>PROPERTY</u>		<u>GENERAL CHARACTERISTIC</u>
Basic weight: 80+/-5 g/m <sup>2</sup>	ISO536	- High density - Good resistance in die-cut pressure
Caliper: 0.110+/-0.005 mm	ISO534	
Color: Light yellow		

### **CAUTION**

1. All technical data statements are typical and should not be used for specification purpose .
2. The product must be stored in shady/ cool place and do not expose to sunlight directly.
3. Before using user shall determine the suitability of the product for their intended use .