

## **TECHNICAL INFORMATION**

**PRODUCT : FLUORESCENT PAPER LABEL – FL**

For product labeling applications which very high adhesion and suitable for attractive and decorative work

### **FACE PAPER**

Type: Fluorescent Paper

<u>PROPERTY</u>		<u>GENERAL CHARACTERISTIC</u>
Basic weight: 80+/-5 g/m <sup>2</sup>	ISO536	- High quality fluorescent paper
Caliper: 0.085+/-0.005 mm	ISO534	- Available in green, chartreuse, orange and red.

### **ADHESIVE**

Type: Acrylic Water Base

<u>PROPERTY</u>		<u>GENERAL CHARACTERISTIC</u>
Adhesion (Stainless Steel): 2.0 kg.f/25mm	FTM2	- Permanent type which high initial tack and high peel adhesive
Loop tack (Glass): 1.6 kg.f/25mm	FTM9	- Good adhesive to metal, plastic, paper, and glass, etc.
Service temperature: min -5°C/ max + 80°C		
Shelf life: 1 year if stored at 22 °C and 50%R.H		

### **LINER**

Type: PE Kraft Release liner

<u>PROPERTY</u>		<u>GENERAL CHARACTERISTIC</u>
Basic weight: 80+/-5 g/m <sup>2</sup>	ISO536	- High density
Caliper: 0.110+/-0.005 mm	ISO534	- Good resistance in die-cut pressure
Color: Light yellow		

### **CAUTION**

1. All technical data statements are typical and should not be used for specification purpose .
2. The product must be stored in shady/ cool place and do not expose to sunlight directly.
3. Before using user shall determine the suitability of the product for their intended use .